



Waugh Rubber Bands
40 Main Road
Tawa
Wellington
Ph: +64 (04) 232 8036
Fax: +64 (04) 232 4859
Email: waughbands@paradise.net.nz
Web: www.waughbands.co.nz

LOOPED WIRE TIES

PRODUCT DESCRIPTION

Double Loop Wire Ties are easy to twist and hard to break which makes them ideal products for a wide and varied range of industries such as farming, orchards/vineyards, manufacturing, civil engineering, building and construction to name a few.

Typical applications include:

- Securing bags or sacks of feed, potatoes, onions, carrots etc.
- Securing of concrete reinforcement bars and mesh in construction and engineering.
- Fencing
- Bundling of bar stock, tubing and pipes etc.
- Securing of supports in orchards/vineyards



SIZE AND RANGE AVAILABILITY

Note: Each roll is packaged individually in a woven bag for protection.

Type / Coating	Length x Wire Thickness (mm)	Quantity per Roll
Galvanised		
	100 x 1.0	2000
	150 x 1.0	2000
	110 x 1.2	2000
	150 x 1.4	2000
	200 x 1.4	2000
	250 x 1.6	2000
	300 x 1.6	2000
PVC Plastic Coated		
Green	110 x 1.6 (1.2mm Wire)	2000
	150 x 1.6 (1.2mm Wire)	2000
Yellow	110 x 1.6 (1.2mm Wire)	2000
Black Annealed		
	100 x 1.6	2000
	150 x 1.6	2000
	150 x 1.6	2000
Copper Coated		
	150 x 1.0	2000

ALSO AVAILABLE

- TWIST TOOLS - Strong, heavy duty 4 spiral wire twist tools with rubber handles.
- GALVANISED WIRE - Limited stock of Ø1.0mm Galvanised wire in 10kg coils (1620m).